


1. General dimensions of the lamp.
2. Follow these steps to secure the base (A) to the lamp's base shaft (B): Loosen the two screws (C) from the base shaft, pass the connection cable (D) through the hole in the base, place the base shaft in the socket of the base, and fasten them with the two screws.
3. In order to install the lampshade (E) on the base shaft (B) it is necessary to loosen the disc (F) and the threaded cap (G) from the base shaft. Then introduce the shade in the threaded tube (H) of the base shaft. Finally, place the disc again and tighten the threaded plug to fasten the shade.

Consumer information:

- Lamps without the IP mark are classed as IP20 and are designed for general interior use, except wet areas (bathrooms, etc.)
- Lamps with the IP mark are designed for exterior use and in wet areas. (E.g. IP54)
- They offer guaranteed protection to people and animals against electrical discharge:
 - Class I: through single electrical insulation and an earthing conductor once correctly connected.
 - Class II: through double electrical insulation.
 - Class III: these kinds of lamps should be connected at very low voltage levels (generally 12V); therefore there is no risk.
- Lamps with this symbol, or without any symbols, can be mounted directly onto normally inflammable surfaces.
- Lamps with this symbol cannot be mounted directly onto normally inflammable surfaces.
 - The safety of this lamp is guaranteed by using a maximum wattage bulb that does not exceed the figure displayed visibly on the lamp.
- The product cannot be treated like conventional domestic waste; it must be taken to the corresponding recycling point for electrical and electronic equipment.

Assembly instructions



B.LUX S.A.

Pol. Ind. Okamika, pab. 1
48289 Gizaburuaga (Bizkaia) Spain
T. (+34) 94 682 72 72
F. (+34) 94 682 49 02
info@grupoblux.com
www.grupoblux.com